

PATENT APPLICATION

DOCKET NUMBER: AN15

TITLED:

Spring Fastener for Connecting Automotive Components and other Articles

OF:

Daniel James Dickinson
Michael Walter Smith
and
Eustathios Vassiliou

"Express Mail" Mailing Label

Number: EU534905755US

Date of Deposit: August 6, 2002

I hereby certify that this paper or fee is
being deposited with the United States Postal
Service "Express Mail Post Office to Addressee"
under 37 CFR 1.10 on the date indicated above
and is addressed to the Commissioner of Patents
and Trademarks, Washington, D.C. 20231

Eustathios Vassiliou

(Typed or printed name of person mailing paper
or fee)

(Signature of person mailing paper or fee)

DOCKET NUMBER: AN15

5. TITLE: Spring Fastener for Connecting Automotive Components and other Articles

RELATED APPLICATIONS

- 10 This application claims priority of provisional patent application 60/323,240, filed on September 19, 2001, which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

- 15 This invention pertains fasteners, and more particularly fasteners which attach one object to another object, with special emphasis to objects in the Automotive Industry.

- 20 BACKGROUND OF THE INVENTION

- In the original conventional technology of fasteners employed to securely attach one object to another, such as for example one part to another in the case of an automobile or an appliance, has utilized a nut on one of the two objects, usually welded or glued to the back of said object, and a bolt passing through a hole on the second object in a manner to be engaged by the nut, thereby securing the two objects together.

- 30 This arrangement presents many problems, among which, one of the most important is that in the case that one object is hollow, the nut has to be in place at the back of the hollow object before assembling the two

objects together. If for any reason the nut is misplaced, and/or if it becomes desirable to introduce a new fastening connection between the two objects, the task of achieving such connection becomes very difficult if not impossible for all practical purposes.

5

The so-called "quick nuts" have also been used to connect two objects. In addition, vibration during the operation of a device, such as an automobile or appliance for example, containing the two objects results very often in loosening of the bolt or "quick nut" and in either full
10 disassembling of the objects from each other, or in a vibration noise which is most annoying and often of unacceptable levels.

Fasteners of the type described in U.S. Patent 4,500,238 (Vassiliou) have been utilized to reduce considerably the potential of bolt or screw
15 loosening and vibration. They have also eliminated the problem of having to place one member of the fastener at the back portion of the hollow object. These fasteners are placed through a slot from the front part of the hollow object. An expanding member, being usually a bolt or a screw, supports the second object by forcing the legs of the fastener (as
20 described for example in U.S. Patent 4,500,238) to open or expand, thereby securing the two objects together. The legs of the fasteners are supported by a double-layered head having an upper side and a lower side joined by side bents. The fasteners of this type have greatly improved the prevailing torque, as well as the pulling force of the system. Prevailing
25 torque is the torque required to render a screw loose. Pulling force is the pulling force applied on the screw to the point of failure, which usually occurs at the bents.

Other references representing the state of the art at this point are
30 disclosed in U.S. Patents 6,179,366 B1, 6,095,734, 5,919,019, 5,873,690,

5,759,004, 5,725,343, 5,636,891, 5,632,584, 5,336,125, 5,314,280,
5,249,900, 5,129,768, 4,610,588, 4,595,325, 4,495,380, 3,505,922,
3,486,158, 3,426,817, 2,707,013, 2,430,555, 2,376,167 and 2,181,966.

5

SUMMARY OF THE INVENTION

This invention pertains fasteners, and more particularly fasteners
which attach one object to another object, with special emphasis to objects
in the Automotive Industry. More particularly, this invention pertains a
10 spring fastener comprising:

a head portion having an upper side, and a lower side, the
upper side having an engageable hole on which a securing member can
engage and pass through;

15

an elastic body disposed at least under the lower side of the
head portion; and

a body portion extending from the lower side of the head
20 portion at a substantially right angle with respect to the head portion, the
body portion comprising

a front body portion and a back body portion, the front
body portion and the back body portion being at least partially
25 in proximity with each other;

a front opening on the front body portion and a back
opening on the back body portion, each of the openings
having a respective opening bottom a respective opening top,
30 a first opening side and a second opening side;

a side body portion on each opening side;

5 a front snapping segment connected to the front body
portion in the vicinity of the opening bottom, and having a
front free engagement end; and

10 a back snapping segment connected to the back
portion in the vicinity of the opening bottom, and having a
back free engagement end.

The presence of the elastic body at least under the lower side
of the head of the fastener is of extreme importance, since, unexpectedly,
in addition to its excellent sealing properties allows the snapping segments
15 to freely pass through the slot of an object, and then to snugly contact the
lower surface of said object, a necessary requirement to prevent
unacceptable rattling.

20 The lower side of the head may have a secondary
engagement section, and at least one of the side body portions may have
a tertiary engagement section.

25 At least one of the free engagement ends may comprise a
section selected from anti-sliding section, anti-opening section, and a
combination thereof.

30 At least one snapping segment may be disposed at least
partially along the respective side body portion and/or the respective
opening.

Vehicles comprising the spring fasteners of this invention, connecting two parts, one of the parts comprising a slot in which the fastener is secured by the snapping segment, are also included within the scope of the instant invention. Thus, automobiles or other vehicles may be made, comprising one or more of the fasteners of the instant invention, providing substantial improvements regarding safety, performance and comfort.

BRIEF DESCRIPTION OF THE DRAWING

The reader's understanding of this invention will be enhanced by reference to the following detailed description taken in combination with the drawing figures, wherein:

FIGURE 1 illustrates a perspective view of a spring fastener in the absence of the elastic body according to a preferred embodiment of the present invention.

FIGURE 2 illustrates a fragmental perspective view of the back body portion and part of the lower side of the head portion of the fastener of Figure 1 in the absence of the elastic body.

FIGURE 3 illustrates a front view of the side body portions comprising threading teeth according to another preferred embodiment of the instant invention.

FIGURE 4 illustrates a front view of a spring fastener of the instant invention, illustrating the elastic body in the region of the head portion.

FIGURE 5 illustrates the operation of the fasteners of the instant invention.

5 FIGURE 6 illustrates a spring fastener according to another embodiment of the present invention in the absence of the elastic body.

FIGURE 7 illustrates a spring fastener according to still another embodiment of the present invention in the absence of the elastic
10 body.

FIGURE 8 illustrates a cross section of a straight snapping segment configuration according to another embodiment of the instant invention.

15 FIGURE 9 illustrates a cross section of a snapping segment configuration involving an anti-opening front engagement end according to another embodiment of the instant invention.

20 FIGURE 10 illustrates a cross section of a snapping segment configuration involving an anti-sliding front engagement end according to another embodiment of the instant invention.

FIGURE 11 illustrates a cross section of a snapping segment
25 configuration involving an anti-sliding front engagement end according to still another embodiment of the instant invention.

FIGURE 12 illustrates a perspective view of a snapping segment configuration involving an anti-sliding front engagement end
30 according to still another embodiment of the instant invention.

FIGURE 13 illustrates a perspective view of a snapping segment configuration involving an anti-sliding front engagement end according to still another embodiment of the instant invention.

5

DETAILED DESCRIPTION OF THE INVENTION

As aforementioned, this invention pertains fasteners, and
10 more particularly fasteners which attach one object to another object, with special emphasis to objects in the Automotive Industry.

As also mentioned earlier, there is a need to have one or more fasteners attached to a large first object, such as a headliner or roof-rack of a car for example, and then attach this large first object to second
15 object, such as the inside or outside of the roof of a car, respectively, for example, by inserting at least part of the fastener into the second object, through a slot for example. An additional requirement many times is to use a rather light force for the insertion, but to require an extraordinarily high
20 force to separate the two objects, if the fastener is not first removed, by unthreading for example a bolt or a screw which attaches the fastener to the first object. A further requirement in many occasions is that after unthreading the bolt or screw, the fastener remains attached to the second object. In other occasions, however, it is required that the two objects are
25 separated by pulling one object away from the other object, without performing other action, such as unthreading a screw or a bolt. Another requirement in a plurality of application is that the fastener has to be attached to a specified position on the first object, and not allowed to turn. The configuration should be such that the screw or bolt could hold
30 additional object(s), such as a car handle for example.

This invention provides fasteners which have the configurations required to satisfy the above need.

5 Referring now to Figure 1, there is depicted, in a perspective view, a spring fastener 10 according to a preferred embodiment of the instant invention. The fastener 10 comprises a head portion 12 having an upper side 14, and a lower side 16. The upper side has an engageable hole 18 on which a securing member 20 (shown in Figure 5) can engage
10 and pass through.

An elastic body 44 (illustrated in Figures 4 and 5), necessary for this invention has been omitted from the rest of the Figures for clarity purposes.

15 The elastic body 44 of this invention, better shown in Figure 4, is disposed at least under the lower side 16 of the head portion 12. Such elastic bodies are preferably integrally molded at least at the lower side of the head portion 12, and preferably around the whole head 12.
20 These elastic bodies are for example disclosed in US Patents 5,725,343, and 6,379,092, both of which are incorporated herein by reference.

In Figure 2, there is depicted a fragmental view of a back lower body 22b as well as portion of the lower head side 16 of the fastener
25 10, as explained hereinbelow.

The spring fastener 10 comprises a body portion 22, which extends from the lower side 16 of the head portion 12 at a substantially right angle with respect to the head portion 12.

30

The body portion 22 has a front body portion 22a (better shown in Figure 1) and the back body portion 22b (better shown in Figure 2). The front body portion 22a and the back body portion 22b are at least partially in proximity with each other.

5

For purposes of clarity, in the following discussion and in the Figures, numerals followed by the letter "a" refer to the front body portion 22a of the body portion 22, and numerals followed by the letter "b" refer to the back body portion 22b of the body portion 22. The two elements
10 corresponding to the body portion 22 are referred to collectively as the respective numeral without the letter.

The front body portion 22a has a front opening 24a, and the back body portion 22b has back opening 24b. Each of the openings 24a
15 and 24b has a respective opening bottom 26a and 26b, and a respective opening top 28a and 28b. Each of the openings 24a and 24b also has a respective first opening side 30a and 30b and a respective second opening side 32a and 32b.

20 The front body portion 22a has side body portions 34a, while the back body portion 22b has side body portions 34b.

The body portion 22 further comprises a front snapping segment 36a connected to the front body portion 22a in the vicinity of the
25 opening bottom 26a, and having a front free engagement end 38a. The body portion 22 also comprises a back snapping segment 36b connected to the back body portion 22b in the vicinity of the opening bottom 26b, and having a back free engagement end 38b.

30 The spring fasteners of the present invention may have a

secondary engagement section at the lower side 16 of the head portion 12. The secondary engagement section 40 comprises two arcs, 40a and 40b, which are capable to engage to the securing member 20 (Figure 5), such as a screw or bolt for example. This arrangement provides increased
5 pulling force, which is the force required to remove the securing member 20 from the spring fastener by pulling them apart.

At least part of the side body portions 34a and 34b may comprise threading teeth 42, which create a tertiary engagement section,
10 as better shown in Figure 3. The threading teeth 42 engage the securing member 20 (Figure 5), thus also providing increased pulling force. The threading teeth may be on the same plane as the respective side body portions 34a and 34b or bent to a certain degree in a manner to nest better the threads of the securing member 20. Further, the angles of the front and
15 the back sides of the teeth may be such as to favor easy insertion and difficult removal of the fastener, in a similar manner as the bent teeth 64 (Figure 13, and applications incorporated by reference) discussed at a later point.

20 Complementary engagement mechanisms which may be used in the present invention, if so desired, are described in provisional applications 60/167,080 (filed 11/23/1999), 60/169,447 (filed 12/07/1999), 60/170,611 (filed 12/14/1999), and 60/179,834 (filed 02/02/2000), and non-provisional application 09/699,760 (filed 10/30/2000), all of which are
25 incorporated herein by reference.

The fastener 10 also has an insertion region 23 (23a and 23b), which may be covered by a soft material, such as a plastic for example, in order to avoid scratching the surface of a part, such as the
30 second object 52 for example shown in Figure 5.

The operation of the above embodiments is better illustrated in Figure 5.

5 The fastener 10 is secured on a first object 46, such as a roof-rack or headliner for example, by passing a securing member, such as a screw or bolt 20, for example, through hole 48 of the first object 46, and threading said screw or bolt 20 on the engageable hole 18. If the secondary and/or tertiary and/or other engagement sections are present,
10 as for example described above, the securing member is engaged on these engagement sections, too.

 The first object 46 has preferably a recessed region 50 under the hole 48, which serves to align and/or nest partially or totally the head
15 portion 12 and/or the elastic body 44. A deeper recessed region 50 allows the distance between the upper side 14 and the lower side 16 of the head portion to be large enough so that the curved regions joining the two sides are adequately gradual, thus providing considerably higher structural strength.

20 One or more additional objects, such as a handle (not shown) for example, may also be secured by the same securing member 20 by passing said securing member through a hole (not shown) belonging to the additional object(s). More than one fasteners may be secured in a similar
25 manner on the first object 46. Such combinations may form an assembly, such as a roof-rack or headliner assembly for example.

 It is important that the length of the securing member is long enough for any desired engagements, but have a shorter length than a

length which would exceed the opening bottom 26, and thus cause any appreciable opening of the body portions 22a and 22b.

The assembly, such as a roof-rack or headliner assembly for example, which usually comprises more than one secured and aligned fasteners 10 in predetermined positions, is pushed by the operator against a second object, such as for example metal sheet 52, which can be in the form of a framework in the vicinity of the roof or ceiling of the outside or inside region of a vehicle for example, having properly arranged slots 54 to accept body portion 22 of the fastener 10. Other material may replace, however, the metal, and it should be understood throughout this disclosure that when referring to metal sheet, any other suitable material may replace the metal, or any other object or combination of objects may replace the sheet.

As the body portion 22 of the fastener 10 is being pushed through the slot 54, the snapping segments 36a and 36b are inwardly pushed until they reach a position at which the body portion is allowed to pass through the slot 54, at which point the elastic body 44 has been compressed to a desired degree. When the body portion 22 of the fastener 10 has reached its final position, the snapping segments 36a and 36b snap back. In sequence, the insertion force is released, allowing the elastic body 44 to expand to a desired degree, and thus, the fastener 10, as well as the whole assembly, are secured onto the metal sheet 52.

The elastic body serves also as an excellent insulator for gases and liquids, and as a noise damper.

A number of parameters determine the force needed to insert the assembly into the slot 54. These include but are not limited to the

thickness, hardness and spring characteristics of the folded sheet metal from which the fastener is made, the shape and dimensions of the fastener, the length and width of the snapping segments, the angle formed by the left and right sections with the respective snapping segments, the dimensions of the slot 62, the thickness and elasticity of the elastic body, etc. For each particular application, these parameters may be determined experimentally, or by engineering calculations, or a combination thereof without undue effort.

10 The force to separate the assembly from the metal sheet 52 is manifold higher than the insertion force, due to the critical configurations of the instant invention, and it depends on the above parameters, but also on the characteristics of the screw or bolt 48, the characteristics of the engageable hole or sections or other engageable elements of the fastener, etc. The multiplicity of engageable features of the fastener of the present invention, are critical in considerably increasing the ratio of the separating force to the insertion force.

20 The utilization of more than one engageable sections is important not only for adequately strong attachment of the fastener 10 to the first object, directly or indirectly, in a manner to form an assembly, but also to combine very easy insertion of the fastener into the slot 54 of the metal sheet 52 with extremely difficult separation of the assembly from the metal sheet after the easy insertion has taken place. The importance of adequately strong attachment, despite the easy insertion, becomes even more important when a larger number of objects, and/or more demanding objects have to be supported by the fastener 10. This is especially so in the case that a given additional object (not shown for purposes of clarity), such as an air-bag system for example, has to be attached to the upper side 56 of the first object 46.

If service is needed, and partial or total removal of the assembly of elements from the metal sheet 52 is needed, the screw(s) or bolt(s) 20 are unthreaded, and the assembly is freed from the metal sheet 52, with the fastener, however, attached now to the metal sheet 52. After the service, the elements may be attached in their initial position by using the screw or bolt 20 as shown in Figure 5.

In a different embodiment of the instant invention, better shown in Figure 6, the snapping segments 36a and 36b are disposed along the side body portions 34a and 34b, respectively. The fastener 10, in this case also, may have secondary and tertiary engagement sections as well as other additional engagement sections (not shown).

The operation of this embodiment is substantially the same as the operation of the above embodiments, with the difference that the snapping segments 36a and 36b are disposed along the side body portions 34a and 34b instead along the opening 24.

In still a different embodiment of the instant invention, better shown in Figure 7, the snapping segments 36a and 36b are disposed not only along the side body portions 34a and 34b, but also along the opening 24 in a continuous manner.

The operation of this embodiment is substantially the same as the operation of the above embodiments, with the difference that the snapping segments 36a and 36b are disposed along the side body portions 34a and 34b, as well as along the opening 24 in a continuous manner.

The snapping segments of this invention may have different configurations, including but not limited to straight and curved.

One example is shown in Figure 8, wherein the snapping
5 segment 36 has a substantially linear configuration with a free engagement end 38 as being a linear extension of the snapping segment 36.

In order to provide anti-opening properties to the snapping segment 36, an anti-opening configuration can be used, such as the one
10 shown in Figure 9, for example. When the snapping segment tends to open, the prong 58, which resides within the slot 54 (Figure 5) during the operation, prevents such opening. This particular configuration is preferable when the failure is due to the snapping segments 36 having a tendency to open (move away from the slot on and parallel to the lower
15 surface 60 of the sheet metal 52) when a separation force is applied between the first object 46 and the metal sheet 52 (see Figure 5)

Anti-sliding properties (preventing the snapping segments 36 from sliding through the slot 54 when a separation force is applied between
20 the first object 46 and the metal sheet 52 - see Figure 5) may be provided, especially in the case that the free engagement end 38 forms an angle with the rest of the engagement segment 36, as illustrated for example in Figure 11, for multi-position engagement on the slot 54. Perspective views of examples of anti-sliding configurations are shown in Figure 12 (ripples
25 62 on the free engagement end 38) and in Figure 13 (bent teeth 64 on the free engagement end 38).

It is important to note that even in the case that the free engagement end 38 is parallel to the side body portions 34 when it resides
30 in the slot 54 (not completely passed through the slot in its final position), it

can hold the first object and the metal sheet together in the case of presence of ripples 62 and/or bent teeth 38.

Further, the securing member 20 itself hinders the sliding of the snapping segments out of the slot 54.

Other examples of anti-opening and anti-sliding configurations, and more details regarding their structure, as well as other types of spring fasteners having snapping segments are disclosed in non-provisional application 09/969,563 (Publication No. 2002/0054808; Publication date: May 9, 2002) and provisional applications 60/246,634 (filed 11/08/2000), 60/249,996 (filed 11/20/2000), 60/267,281 (filed 02/08/2001), 60/283,266 (filed 04/12/2001), 60/289,343 (filed 05/07/2001), 60/302,194 (filed 06/29/2001), 60/301,164 (filed 06/25/2001), 60/308,921 (filed 07/31/2001), 60/310,343 (filed 08/06/2001), and 60/312,867 (filed 08/16/01), all of which are incorporated herein by reference.

Vehicles comprising the spring fasteners of this invention, connecting two parts, one of the parts comprising a slot in which the fastener is secured by the snapping segment, are also included within the scope of the instant invention. Thus, automobiles or other vehicles may be made, comprising one or more of the fasteners of the instant invention, providing substantial improvements regarding safety, performance and comfort.

Examples of embodiments demonstrating the operation of the instant invention, have now been given for illustration purposes only, and should not be construed as restricting the scope or limits of this invention in any way.

Any feature(s) described in one of the exemplary embodiments may be combined with any features incorporated in any other exemplary embodiment according to this invention.

- 5 Any explanations given are speculative and should not restrict the scope of the claims.